

APR 02 2009

FACSIMILE COVER SHEET

Date: April 2, 2009
To: Examiner William E. Dondero
at the U.S. Patent and Trademark Office
Fax No: 571-273-8300
From: Heidi A. Dare
Tel. No: 312-321-4809

**BRINKS
HOFFER
GILSON
& LIONE®**

A Professional Corporation
Intellectual Property
Law Worldwide

Attorney Docket No. No.: 12706-15

Re: **U.S. Application No. 10/526,253**
Apparatus for and a Method of Adjusting
the Length of an Infusion Tube

No. of Pages
(incl. this page): 2

Confirmation Copy To Follow: Yes No X

IF YOU HAVE ANY PROBLEMS RECEIVING THIS MESSAGE,
PLEASE CALL 312-245-3455 AND ASK FOR: Lisa Hedl.

THIS MESSAGE IS INTENDED ONLY FOR THE INDIVIDUAL OR ENTITY TO WHICH IT IS ADDRESSED. IT MAY CONTAIN PRIVILEGED, CONFIDENTIAL, ATTORNEY WORK PRODUCT, OR TRADE SECRET INFORMATION WHICH IS EXEMPT FROM DISCLOSURE UNDER APPLICABLE LAWS. IF YOU ARE NOT THE INTENDED RECIPIENT, OR AN EMPLOYEE OR AGENT RESPONSIBLE FOR DELIVERING THE MESSAGE TO THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION, OR COPYING OF THIS MESSAGE IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS MESSAGE IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE AND RETURN THE ORIGINAL MESSAGE (AND ALL COPIES) TO US BY MAIL AT THE ABOVE ADDRESS. WE WILL REIMBURSE YOU FOR POSTAGE.

COVER MESSAGE:

Please see attached.

1. (Currently Amended) An apparatus for adjustment of the length of an infusion tube comprising:

a first wall;

a second wall;

at least one elongate slot arranged in at least one of said walls such that an infusion tube can pass through said wall, the slot sized to have a length which is greater than or equal to the diameter of the infusion tube, said at least one slot extending from a periphery of the wall radially towards a center of the wall;

at least one connecting element connecting said first wall to said second wall, said connecting element being secured at a distance to a peripheral circumference of the walls; and

an inlet opening extending around the connecting element, said opening being provided by a distance between said walls in a radial distance to said connecting element, inner faces of the first and the second walls converge from the connecting element towards the inlet opening, said opening having a width (M) measured between the walls, the width M sized to allow passage of a single infusion tube through the inlet opening.